

INLINE MODELS

- Appliance Gray finish
- Maximum working temperature: 200°F.
- Maximum working pressure: 100 PSIG
- **Third party certified to NSF/ANSI61&372**




ANSI/NSF 61



Shipping Part Number	System Dimensions (ins)		Total Precharge Volume (gal)	Max Accept Factor	Drawdown (gal)			Shipping Wt (Vol) lbs (cu ft)	Pallet Qty	System Conn. NPTM	Precharge Pressure (psig)
	Dia	Height			20/40	30/50	40/60				
SL2I	8	12 5/8	2.0	0.45	0.8	0.7	0.6	5 (0.6)	75	3/4"	18
SL4I	11	15	4.4	0.55	1.8	1.5	1.3	9 (1.2)	48	3/4"	18
SL8I	11	22 1/4	7.4	0.43	3.1	2.6	2.2	15 (2.0)	32	3/4"	28
SL10I	15 3/8	17 3/4	10.3	1.00	4.1	3.5	3.0	20 (3.0)	18	1"*	38
SL14I	15 3/8	22	14.0	0.81	5.6	4.8	4.1	22 (4.1)	18	1"*	38

* NPTF connection.



VERTICAL STAND MODELS


- Appliance Gray finish
- Malleable elbow system connection.
- Maximum working temperature: 200°F.
- Maximum working pressure: 100 psig
- **Third party certified to NSF/ANSI 61&372.**



ANSI/NSF 61



Part Number	Dimensions (ins)		Total Volume (gal)	Max Accept Factor	Drawdown (gal)			Shipping Wt (Vol) lbs (cu ft)	Pallet Qty	System Conn. NPTF	Precharge Pressure (PSIG)
	Dia	Height			20/40	30/50	40/60				
SL14V	15 3/8	25 1/8	14.0	0.81	5.6	4.8	4.1	25 (3.8)	18	1"	38
SL20V	15 3/8	32 1/8	20.0	0.57	8.0	6.8	5.9	33 (4.9)	18	1"	38
SL32V	15 3/8	46 1/2	32.0	0.35	-	10.9	9.4	43 (7.0)	9	1"	38
SL34V	22	29 5/8	34.0	1.00	13.7	11.6	10.0	61 (9.5)	4	1 1/4"	38
SL44V	22	36	44.0	0.77	17.7	15.0	12.9	69 (11.0)	4	1 1/4"	38
SL62V	22	46 3/4	62.0	0.55	24.9	21.1	18.2	92 (13.9)	4	1 1/4"	38
SL86VS	26	47 1/4	86.0	0.54	34.6	29.2	25.3	123 (18.9)	4	1 1/4"	38
SL119V	26	61 7/8	119.0	0.39	-	40.5	35.0	166 (24.5)	4	1 1/4"	38



HORIZONTAL PUMP STAND MODELS

- Appliance Gray finish
- Maximum working temperature: 200°F.
- Maximum working pressure: 100 PSIG
- **Third party certified to NSF/ANSI 61&372.**



ANSI/NSF 61



Part Number	Dimensions (ins)			Total Volume (gal)	Max Accept Factor	Drawdown (gal)			Shipping Wt (Vol) lbs (cu ft)	Pallet Qty	System Conn. NPTM	Precharge Pressure (psig)
	H	W	L			20/40	30/50	40/60				
SL14H	16	15 3/8	20 7/8	14.0	0.81	5.6	4.8	4.1	29 (4.0)	18	1"	38