



Clear Braided PVC Hose Standard Wall, Class 125 Features:



- Flexible, see through clear hose with braid pattern reinforcement of two polyester spirals.
- Flexible clear PVC NSF 51 certified to 100°F (38°C), USP CLASS V1 rated.
- All hose compound ingredients used are listed in US FDA CFR, Title 21.
- Temperature range + 25° to 150° F / -5° to +65°C.
- Silicone free.
- Food and beverage grade, standard wall.
- Use for air, water lines.

Part Number	Nominal (inches)		Max Working Pressure		Reel Length	Approx Wt per CFT.	List Price Per Reel
	ID	OD	PSI@68°F	PSI@122°F			
CBH25-1	1/4	0.438	250	105	100'	5.7 lbs	\$ 159.47
CBH38-1	3/8	0.594	225	97	100'	9.0 lbs	222.25
CBH50-1	1/2	0.750	200	86	100'	13.8 lbs	305.16
CBH58-1	5/8	0.875	200	86	100'	16.5 lbs	363.39
CBH75-1	3/4	1.030	150	65	100'	21.9 lbs	457.68
CBH100-1	1	1.300	125	54	100'	31.5 lbs	568.16
CBH100-2	1	1.300	125	54	200'	31.5 lbs	1061.98
CBH125-50	1 1/4	1.625	100	43	50'	45.0 lbs	559.55
CBH125-1	1 1/4	1.625	100	43	100'	45.0 lbs	1119.14
CBH150-50	1 1/2	1.937	100	43	50'	64.0 lbs	711.96
CBH150-1	1 1/2	1.937	100	43	100'	64.0 lbs	1423.86
CBH200-1	2	2.490	75	33	100'	95.0 lbs	2284.55

**** Temperatures higher than 68° F reduce available working pressure. See next page for temperature, working pressure calculation chart and cautionary note.**