





## Heat Shrink Splicing Kit Features:

· Excellent dielectric strength and can be shrunk over a large diameter connector and still effectively seals watertight down to a small diameter cable.



- No grease tape or epoxy is needed.
- · Highly resistant to moisture, fungus and weathering.
- Supplied w/ EC1410 wire connectors for #14-#10 gauge wire. (EC6/8 for LHS Series.) •
- Private labeling available for minimum orders of 200 kits.
- Bulk tubing available. •
- Third party certified to NSF/ANSI 372.

## Wire Connector Features:

- · Provides quick, safe and sure electrical connection.
- Seamless. •

• 13/16" in length.

| Part Number   | Tubes Fits            | # Tubes |               | Ctn Qty | List Price |
|---|-----------------------|---------|---------------|---------|------------|
| Wire Size (included in kit)   Black Heavy Wall Heat Shrink Kits (included in kit) |                       |         |               |         |            |
| •   |                       | 0       | 0             | ГО      | ¢ 0.07     |
| HS2   | #14, #12, #10         | 2       | 2             | 50      | \$ 3.97    |
| HS3   | #14, #12, #10         | 3       | 3             | 50      | 5.70       |
| HS3-4   | #14, #12, #10         | 3       | 4 4           | 50      | 5.98       |
| HS4   | #14, #12, #10         |         |               | 50      | 6.49       |
| LHS3  | #8, #6, #4, #2        | 3       | 3 (#8) 3 (#6) | 20      | 14.86      |
| LHS4  | #8, #6, #4, #2        |         | 4 (#8) 4 (#6) | 20      | 19.61      |
| CHST  | #14, #12, #10         | BULK    | 0             | 500     | 1.32       |
| Black Standard Wall Heat Shrink Kits  |                       |         |               |         |            |
| HSSW2   | #14, #12, #10         | 2       | 2             | 50      | 2.99       |
| HSSW2-3   | #14, #12, #10         | 2       | 3             | 50      | 3.27       |
| HSSW3   | #14, #12, #10         | 3       | 3             | 50      | 4.32       |
| HSSW4   | #14, #12, #10         | 4       | 4             | 50      | 5.61       |
| CHSSWT  | #14, #12, #10         | BULK    | 0             | 500     | 0.97       |
|   | ll Heat Shrink Kits   |         |               |         |            |
| HSHWC2  | #14, #12, #10         | 2       | 2             | 50      | 3.88       |
| HSHWC2-3  | #14, #12, #10         | 2       | 3             | 50      | 4.78       |
| HSHWC3  | #14, #12, #10         | 3       | 3             | 50      | 5.52       |
| HSHWC3-4  | #14, #12, #10         | 3       | 4             | 50      | 5.74       |
| HSHWC4  | #14, #12, #10         | 4       | 4             | 50      | 7.07       |
| LHSHWC3   | #8, #6, #4, #2        | 3       | 3 (#8) 3 (#6) | 20      | 14.86      |
| LHSHWC4   | #8, #6, #4, #2        | 4       | 4 (#8) 4 (#6) | 20      | 21.06      |
| CHSHWCT   | #14, #12, #10         | BULK    | 0             | 500     | 1.19       |
| Clear Standard Wall Heat Shrink Kits  |                       |         |               |         |            |
| HSCL2   | #14, #12, #10         | 2       | 2             | 50      | 3.35       |
| HSCL3   | #14, #12, #10         | 3       | 3             | 50      | 4.96       |
| HSCL3-4   | #14, #12, #10         | 3       | 4             | 50      | 5.33       |
| HSCL4   | #14, #12, #10         | 4       | 4             | 50      | 6.62       |
| CHSCLT  | #14, #12, #10         | BULK    | 0             | 500     | 1.04       |
| Wire Connecto   | ors                   |         |               |         |            |
| EC1410  | For #14-10 gauge wire |         |               | 100     | 51.00/100  |
| EC8   | For #8 gauge wire     |         |               | 250     | 0.84 each  |
| EC6   | For #6 gauge wire     |         |               | 250     | 1.38 each  |
| EC4   | For #4 gauge wire     |         |               | 100     | 2.18 each  |
| EC2   | For #2 gauge wire     |         |               | 100     | 2.92 each  |





**EC Series** 



NO LEAD

v

EAD-FREE