



HROK4



HROK5



HARVARD Residential Reverse Osmosis System Features:



- Pre-assembled, easy to install 4 or 5 stage RO system.
- Complete with all installation accessories and instructions.
- High rejection, thin film membrane up to 98% efficient with 50 gal/day (4 stage) or 75 gal/day (5 stage) capacity. (Note: Feed water requirements below)
- NSF Standard 58 listed, CE certified, polypropylene tank rated to 100 psi.
- All fittings, tubing, housings, valves, cartridges and membranes are NSF listed or made from NSF listed materials.
- Automatic shut-off valve made from NSF listed materials.
- Lead free, long reach chrome faucet included. Meets California AB1953 requirements.
- Cartridges, valves, fittings, sump wrench, white mounting bracket and complete installation instructions included.

NOTE: Every HROK, HROK-BP has been pressure and water tested after assembly. Due to the variety of installation methods, environments and systems components, standard AGI warranty does not apply to HROK, HROK-BP systems or components.

Feed Water Requirements:

- Maximum TDS: 2,000 ppm
- Maximum Iron: 0.3 ppm
- Maximum hardness: 12 gpg
- Temperature: 45-100°F
- Maximum hydrogen sulfate: 0
- Maximum manganese: 0.05 ppm
- Pressure: 40-85 psi (min/max)
- pH: 4-10

HROK Systems Include:

- NSF listed John Guest style quick connect fittings.
- Filter housings made from NSF listed materials.
- NSF Standard 58, CE listed polypropylene tank. (10" diam x 15" high)
- 5 micron sediment pre-filter cartridge.
- Activated GAC granular carbon cartridge (5 stage)
- Activated carbon block cartridge.
- NSF listed Dow/Filmtec thin film membrane. 50 gpd (4 stage) 75 gpd (5 stage).
- Inline post carbon polishing cartridge.
- Automatic shutoff valve made with NSF materials.
- Long reach, lead free chrome faucet, meets California AB1953.
- Sump wrench, tubing, service valve, check valve, ball valves, flow restrictor included.
- Complete installation instructions.
- 5 stage with booster pump for sink water pressure lower than 40 psi.
- Booster pump rated to 125 psi with 110V/60 Hz, 24VDC power.

Note: For cold water use only. Do not install on hot water line. To insure that the membrane is functioning properly, the product water must be tested regularly.

The Benefits (nominal ion rejection characteristics)*

Aluminum	96-98%	Manganese	96-98%
Ammonium	80-90%	Mercury	94-97%
Borate	30-50%	Nickel	96-98%
Boron	50-70%	Nitrate	90-95%
Bromide	90-95%	Orthophosphate	96-98%
Cadmium	93-97%	Phosphate	95-98%
Calcium	93-98%	Polyphosphate	96-98%
Chloride	92-95%	Potassium	92-96%
Chromate	85-95%	Radioactivity	93-97%
Copper	96-98%	Silica	80-90%
Cyanide	85-95%	Silicate	92-95%
Fluoride	92-95%	Silver	93-96%
Hardnes Ca & Mg	93-97%	Sodium	92-98%
Iron	96-98%	Sulfate	96-98%
Lead	95-98%	Thiosulfate	96-98%
Magnesium	93-98%	Zinc	96-98%

* The above percent rejection is for reference only. Actual rejection will depend heavily on the exact chemistry, temperature, pressure & TDS content of the feed water.

Part No.	Description
HROK4	4 stage RO system, 50 gpd
HROK5	5 stage RO system, 75 gpd
HROK5BP	5 stage RO system, 75 gpd w/ booster pump
HROK4MEM50	Dow/Filmtec TFC membrane 50 gpd
HROK5MEM75	Dow/Filmtec TFC membrane 75 gpd
HROKTANK32	3.2 gal plastic tank, NSF58/CE
HROKASV	Auto shutoff valve