

VIPERT[™] Potable Tubing







VIPERT[™] Potable Tubing Features:

- VIPERT polyethylene raised temperature tubing is based on patented technology and made with Hypertherm PE-RT resins from The Dow Chemical Company.
- VIPERT provides increased flexibility and excellent hydrostatic strength at high temperatures and burst pressures that surpass required industry standards.
- Offers improved flexibility with relaxed memory for less spring back than PEX. Maintains excellent flexibility in extreme cold or hot environments.
- Compatible with all popular fittings systems: F-1960, F-1807 and F-2159
- · Can be used with cold expansion, crimp, brass and push fittings.
- VIPERT is recyclable and requires less energy to produce than PEX.
- 25 year warranty.
- 100 PSI@180°F, 200 PSI@73°F SDR-9
- CSA B137.18
- ASTM D2769, ASTM E84
- CAN/ULC S101/UL263, CAN/ULC S102.2-03

STANDARD AGI DISCOUNTS DO NOT APPLY. Contact your sales representative for pricing.







* Minimum order 20 assorted CANPEX/VIPERT bundles shipped to one location.

Nominal			Bundle	PART NUMBER per COLOR			
Size	Туре	Length	Qty *	WHITE	RED	BLUE	List Price
VIPERT™	POTABLE	TUBING					
1/2"	Sticks	10'	500'	PRT3L-S	PRTR3L-S	PRTB3L-S	\$ 1.02/ft
1/2"	Sticks	20'	500'	PRT3L5	PRTR3L5	PRTB3L5	1.02/ft
1/2"	Coil	100'		PRT3C1	PRTR3C1	PRTB3C1	0.96/ft
1/2"	Coil	250'			PRTR3C2.5	PRTB3C2.5	0.96/ft
1/2"	Coil	300'		PRT3C3	PRTR3C3	PRTB3C3	0.96/ft
1/2"	Coil	500'		PRT3C5	PRTR3C5	PRTB3C5	0.96/ft
1/2"	Coil	1000		PRT3C10	PRTR3C10	PRTB3C10	0.96/ft
3/4"	Sticks	10'	250'	PRT4L-S	PRTR4L-S	PRTB4L-S	1.77/ft
3/4"	Sticks	20'	200'	PRT4L2	PRTR4L2	PRTB4L2	1.77/ft
3/4"	Coil	100'		PRT4C1	PRTR4C1	PRTB4C1	1.67/ft
3/4"	Coil	250'			PRTR4C2.5	PRTB4C2.5	1.67/ft
3/4"	Coil	300'		PRT4C3	PRTR4C3	PRTB4C3	1.67/ft
3/4"	Coil	500'		PRT4C5	PRTR4C5	PRTB4C5	1.67/ft
3/4"	Coil	1000'		PRT4C10	PRTR4C10	PRTB4C10	1.67/ft
1"	Sticks	10'	100'	PRT5L-S	PRTR5L-S	PRTB5L-S	3.21/ft
1"	Sticks	20'	100'	PRT5L1	PRTR5L1	PRTB5L1	3.21/ft
1"	Coil	100'		PRT5C1	PRTR5C1	PRTB5C1	3.03/ft
1"	Coil	300'		PRT5C3	PRTR5C3	PRTB5C3	3.03/ft
1"	Coil	500'		PRT5C5	PRTR5C5	PRTB5C5	3.03/ft
1"	Coil	1000'		PRT5C10			3.03/ft
11/4"	Sticks	20'	100'	PRT6L1	PRTR6L1	PRTB6L1	6.45/ft



NO LEAD

< 0.25% Pb by weighted avg

Third Party Certified