



AGDUCT / HDT / EDT Series

Meets UL723

ISO 9001

Contractor/Industrial Grade Cloth Reinforced Duct Tape Features:

- Multi-purpose duct tapes.
- Polyethylene coated cloth backing.
- Natural rubber based adhesive.
- Temperature range: 40°F to 200°F.
- Superior tensile strength, adhesion and tack.
- For seaming, sealing and hanging polyethylene or vinyl.
- HDT Series recommended for pool liner installations.
- Conformable and will not curl or twist during application.
- Manufactured for AGI in an ISO9001 facility.

Part Number	Thickness	Width x Length	Color	Ctn Qty
EDT260	7.5 mil	48mm x 55m (2" x 60 yds)	Silver	24
AGDUCT	9 mil	48mm x 55m (2" x 60 yds)	Silver	24
HDT260	10 mil	48mm x 55m (2" x 60 yds)	Silver	24
HDT260 BLUE	10 mil	48mm x 55m (2" x 60 yds)	Blue	24
HDT260 RED	10 mil	48mm x 55m (2" x 60 yds)	Red	24
HDT260 BLACK	10 mil	48mm x 55m (2" x 60 yds)	Black	24
HDT260 WHITE	10 mil	48mm x 55m (2" x 60 yds)	White	24

Part Number	Adhesive	Total Thickness (mil)	Tensile Strength (lb/in)	Adhesion to Steel (oz/in)	Flame Spread	Smoked Developed Index
EDT260	Rubber	7.5	19.0	28	--	--
AGDUCT	Rubber	9.0	29.0	45	--	--
HDT260	Rubber	10.0	24.0	60	10	5