



RPS75

RPS75™ Rotor

The RPS75™ gear drive is designed for basic residential and light commercial applications and is a direct replacement for Hunter® PGP® rotors. The reversing mechanism, a K-Rain patented feature, is the same mechanism used in the Hunter PGP (K-Rain currently licenses this patent to Hunter.) With K-Rain's wide selection of standard and low angle nozzles, the RPS75 provides even water distribution.

Features:

- Direct Replacement for Hunter® PGP®.
- Right Position Start - Rotor rotates counterclockwise from fixed right start position.
- Riser Fits in Existing Hunter PGP Cans - Simply unscrew the existing riser from the PGP can and replace with the RPS75 riser.
- Top Adjustment - No training necessary, the RPS75 has the same adjustment procedure as the Hunter PGP.
- Full and Part Circle Rotation - Provides a full range of adjustment from 40° to 360°
- Non-Flushing Wiper Seal - Reduces leaks caused by debris trapped under seal.
- 3/4" Inlet - Replaces all standard rotors.
- Ideal for Low Flow Applications.
- Universal Adjustment Tool - Compatible with existing Hunter products.
- Rubber Cover - Seals out dirt and increases product durability.
- Wide Selection of Nozzles - Including standard and low angle, provides flexibility in system design.
- **Key and check disc also included in master cases.**
- **FULL 5 YEAR WARRANTY. Subject to all standard warranty conditions that apply to all K-Rain rotors.**



Find performance data on following page.



ARC selection 40°- 360°. Adjusts from RIGHT start.

Specifications:

- Inlet 3/4" female threaded NPT
- Arc Adjustment Range: 40° to 360°
- Flow range: 0.75 - 8.2 GPM
- Pressure Rating: 30-70 PSI
- Precipitation Rate: 0.12 to 1.16 inches/hour
- Overall height popped down : 7 3/8"
- Recommended spacing: 25' to 45'
- Radius: 22' to 51'
- Nozzle trajectory: 25° standard or 11° low angle
- 8 standard and 4 low angle nozzles included
- Riser Height: 4"

Part Number	Description	Ctn Qty	List Price
RPS75	RPS Standard Rotor	20	\$ 26.37