



13003

MiniPro™ Rotor

Perfect for small lawn and landscape areas and for replacing fixed sprays.
Direct replacement for the Toro Mini8.

Features:

- Gear driven, rotary type sprinkler capable of covering an area of 17' to 30'.
- Revolutionary patented easy arc set is easily adjusted from the top with a flat blade screwdriver. Stainless steel radius adjustment screw.
- Adjustable rotation provides a full range of adjustments from 40° to 360°. Patented arc set degree markings clearly indicate current watering pattern and simplifies adjustment
- Adjustable in all phases of installation - before, after while static or while in operation.
- Time proven patented reversing mechanism assures continuous reverse and return.
- Ratcheting riser easily adjusts your left start position by turning the riser.
- Supplied with 5 numerically coded interchangeable nozzles. Wide selection of nozzles provides flexibility in system design to achieve matched precipitation.
- Heavy duty rubber cover seals out dirt and increases durability.
- **FULL 5 YEAR WARRANTY. Subject to all standard warranty conditions that apply to all K-Rain rotors.**



Specifications:

- Inlet 1/2" NPT
- Arc adjustment range 40° to 360°
- Flow range: 0.75 - 3.3 GPM
- Pressure Rating: 20-70 PSI
- Precipitation Rate: 0.22 to 0.41 inches/hour (depending on spacing and nozzle used)
- Overall height popped down : 6"
- Recommended spacing: 17' to 28'
- Radius: 17' to 30'
- Nozzle trajectory: 26°
- Riser Height: 4", 6" or 12".



Find performance data on following page.



ARC selection 40° - 360°.
Adjusts from LEFT start.

Part Number	Description	Ctn Qty	List Price
13003	MiniPro short range rotor 4"	25	\$ 28.04
13006	MiniPro short range rotor 6"	20	41.74
13012	MiniPro short range rotor 12"	12	69.92