



7101 and 7101-J Series



No tools needed with Jar Top



Manual External Bleed Screw

Pro Series 150 1" Solenoid Valves

Offer the professional a wide array of features and benefits.
Use for residential, light commercial, dirty water applications.



Features:

- Heavy duty, corrosion & UV resistant PVC construction increases the life of the valve.
- External bleed screw with removable metering pin allows for cleaning of the pin without disassembling the valve.
- **Threaded jar top** allows for quick removal of the cap for easy servicing. The glass filled nylon screw cap increases durability.
- **7101-J Series is direct replacement for Irritrol 2400.**
- Manual external bleed screw allows for manual operation in system start-up.
- Manual internal bleed through solenoid allows for manual operation without leaking water.
- Captured plunger solenoid allows for the solenoid to be removed without losing the plunger.
- 5 year Limited Warranty.

Specifications:

- Dimensions: 5 1/4" H x 3 1/8" W x 5" 5 1/4" H x 3" W x 4 3/8" Jar Top
- Flow range: 0.25-30 GPM
- Pressure Rating: 10-150 PSI
- Solenoid: 24 VAC 60 cycle
- Inrush Current: 0.4 Amps
- Holding Current: 0.2 Amps

Performance Data:

GPM	5	10	15	20	30
ProSeries 150 1" valve					
PSI LOSS	2.9	2.1	1.8	3.0	5.0
ProSeries 150 1" valve with jar top					
PSI LOSS	3.3	3.9	2.9	3.2	6.1

Part Number	Description	Ctn Qty	List Price
7101	1" Female thread NPT	12	\$ 43.49
7101-SL	1" Female Slip	12	44.38
7101-J	1" Female Thread Jar Top, NPT	12	43.50
7101-J-SL	1" Female Slip Jar Top	12	44.38