



2000 Series

2000 Series Single Station Controller

Single station controllers stay safe with rain-tight enclosures.



Features:

- 24 hour programmable time dial with multiple start times and a wide variety of timing periods including skip-a-day 14 day program.
- UL approved components.
- Perfect for nursery or mist applications.
- 2200 models have 10 minute programmable dial with a wide variety of timing periods in multiples of 1.5, 3 and 6 seconds and multiple start times.
- 2500 models are prewired for easy connection of a rainswitch and allows manual override of rainswitch from controller face.
- 2520 model allows operation of 24 volt rainswitch and 2 hp 220 volt pump with same controller.
- 2 year Limited Warranty.

Part Number	Voltage Input	Voltage Output	Rating	Ctn Qty
2100 Single Station Controllers				
2110	110 VAC, 60 Hz	110 VAC, 60 Hz	Single Pole, up to 1 HP	6
2112	110 VAC, 60 Hz	110 VAC, 60 Hz	Double Pole, up to 2 HP	6
2114	110 VAC, 60 Hz	24 VAC, 30 VA	Built in Transformer	6
2120	220 VAC, 60 Hz	220 VAC, 60 Hz	Double Pole, up to 2 HP	6
2200 Short Duration Single Station Controllers				
2210	110 VAC, 60 Hz	110 VAC, 60 Hz	up to 1 HP	6
2214	110 VAC, 60 Hz	24 VAC, 30 VA	Built in transformer	6
2500 Rainswitch Ready Controllers				
2510	110 VAC, 60 Hz	110 VAC, 60 Hz	Double Pole, up to 2 HP	6
2514	110 VAC, 60 Hz	24 VAC, 30 VA	Built in transformer	6
2520	220 VAC, 60 Hz	220 VAC, 60 Hz	Double Pole, up to 2 HP	6