


**JL355 Series**
**4**

## V-2® Multi Purpose PTFE Thread Sealant

A soft setting, non-petroleum based thread sealant for use where immediate pressurization is desired. Non-staining, low odor, off white color. Use on all types of metals, reinforced fiberglass and PVC. **MIL-TT-S-1732.**

**USDA H-2 Authorized. IAPMO Approved.**


**ISO 9001**

Part Number	Net Contents & Container Type	Shipping Weight/Case	Case Equivalents	Case Qty	List Price
JL35502	1/2 pint brush top can	11 lbs.	1	12	\$ <b>89.86</b>
JL35504	1 pint brush top can	19 lbs.	1	12	114.26


**JL240 Series**
**4**

## TFW™ Anti-Sieze Thread Sealant with PTFE

Low friction and non-toxic, TFW is used to prevent thread leaks of almost all fluids, gases or steam, even at temperatures up to 500 F. Can be used on metal, PVC, ABS and CPVC fittings and piping. **IAPMO approved.**

Part Number	Net Contents & Container Type	Shipping Weight/Case	Case Equivalents	Case Qty	List Price
JL24002	1/2 pint brush top can	9 lbs.	1	12	\$ <b>71.24</b>
JL24004	1 pint brush top can	17 lbs.	1	12	98.26


**JL23023**
**4**

## TF-15® Thread Sealant with PTFE for fiberglass pipe

High pressure thread sealant containing PTFE and EP additives that allow for easy breakout without seizing, stripping or galling. Highly recommended for use as a sealant on fiberglass tubing and casing threads. **Passes California COR Title 22**

Part Number	Net Contents & Container Type	Shipping Weight/Case	Case Equivalents	Case Qty	List Price
JL23023	1 gal pail	11 lbs.	1	1	\$ <b>479.09</b>


**JL72542**
**5**

## Clean-Up Plus™ Organic Solvent Cleaner

Environmentally safe cleaner and degreaser. Blend of organic solvents, safe non-flammable CO2 propellant. Citrus scent. Residue free product is safe on all metals. 29KV dielectric strength. No Tri 1-1-1. **USDA authorized.**

Part Number	Net Contents & Container Type	Shipping Weight/Case	Case Equivalents	Case Qty	List Price
JL72542	15 oz. aerosol	16 lbs.	1	12	\$ 56.35


**JL61542**
**5**

## Clean-Up™ Industrial Cleaner and Safety Solvent

Heavy duty low foaming cleaner/degreaser. Fast working, non-flammable residue free product formulated with an ozone friendly chlorinated solvent. 29 KV dielectric strength. No Tri 1-1-1.

Part Number	Net Contents & Container Type	Shipping Weight/Case	Case Equivalents	Case Qty	List Price
JL61542	18 oz. aerosol	15 lbs.	1	12	\$ <b>64.21</b>


**JL16041**
**5**

## Moly Mist™ Dry Film Lubricant

Use to break in equipment and assemble moving parts. Micro-fine molybdenum disulfide suspended in a quick-drying carrier. Bonds to any surface in seconds to provide low coefficient of friction, extended lubrication and improved operation.

Part Number	Net Contents & Container Type	Shipping Weight/Case	Case Equivalents	Case Qty	List Price
JL16041	12 oz. aerosol	13	1	12	\$ 71.55