

Foot & Check - Plastic



HARVARD Four in One Plastic Foot Valve

- Positive sealing spring loaded valve poppet closes against a smooth tapered seat.
- Corrosion resistant nylon body and internals.
- Self cleaning design for continuous positive sealing.
- Large screen designed to assure smooth water passage and better suction.
- Tapered screen eliminates pipe joint hang-ups during installation.
- Fits four pipe sizes., 3/4" through 1 1/2".
- Third party certified to NSF/ANSI 372.

HARVARD
LOW-LEAD IAPMOR&T
No LEAD < 0.25% Pb by weighted avg Third Party Certified to NSF / ANSI 372

Part Number	Size	Ctn Qty	List Price
FV441	3/4" through 1 1/2"	100	\$ 18.63

FV441



FV Series



LC Series



FV SN Series

Brady Plastic Foot & Check Valve Features:

- "Nose Cone" diffuser reduces friction.
- 50% greater water flow.
- Acetal copolymer construction.
- Non-electrolytic, non-corrosive.
- Spring loaded, 316 stainless steel
- BUNA-N seal
- Pressure max: 175 psi
- Temperature max: 180 F
- LC check valve, FPT x FPT
- Third party certified to NSF/ANSI 372.

Part Number	Size	Ctn Qty	List Price
Brady Foot Valve -	Spring Loaded		
FV75	3/4"	125	\$ 39.66
FV100	1"	100	45.51
FV125	1-1/4"	50	64.70
FV150	1-1/2"	50	78.57
Brady Check Valve	e- Spring Loaded		
LC75	3/4"	24	34.50
	- 11		

LC75	3/4	24	34.50
LC100	1"	24	38.12
LC125	1-1/4"	24	56.10
LC150	1-1/2"	12	67.20

Brady Foot Valve Strainer

FV75SN	3/4"	50	3.56
FV100SN	1"	50	5.01
FV125SN	1-1/4"	50	5.81
FV150SN	1-1/2"	50	5.44





