

## PFOA/PFOS Filtration Systems Features:

- Professional grade PFOA/PFOS reduction systems for whole house or point of use undersink applications.
- Systems are certified by IAPMO R&T to reduce up to 98% of PFOA/PFOS, commonly known as “forever chemicals”.
- Complete systems include housing, cartridge, wrench, mounting bracket with screws and installation and operation manual.
- Integrated pressure relief valve for easier cartridge change-outs.

**NEW**


Systems Certified by IAPMO R&T to NSF/ANSI 53



## CHLORPLUS PROTECT™ System Features:

- For undersink point of use.
- 10" filter housing
- 3/4" FPT inlet
- Maximum 1 gpm service flow rate.
- Also features premium sediment, chlorine and chloramine reduction.



| Part No.  | Description                                  | Ctn | Cty |
|-----------|--|-----|-----|
| 150742    | Chlorplus™ Protect 10" undersink system kit  | 1   |     |
| 655226-43 | Chlorplus™ Protect 10" replacement cartridge | 12  |     |



## FLOPLUS PROTECT System Features:

- Whole house use.
- 20" filter housing
- 1 1/4" FPT inlet
- Maximum 5 gpm service flow rate.
- Maximum filtration with minimum pressure drop.



| Part No.  | Description                                  | Ctn | Cty |
|-----------|--|-----|-----|
| 150736    | FloPlus Protect 20"BB whole house system kit | 1   |     |
| 655223-43 | FloPlus Protect 20" BB replacement cartridge | 6   |     |

## Specifications:

| SYSTEM                 | CHLORPLUS          | FLOPLUS                |
|------------------------|--------------------|------------------------|
| Housing Size:          | 10" Heavy Duty     | 20" Heavy Duty         |
| Inlet Size:            | 3/4" FPT           | 1 1/2" FPT             |
| Flow Rate:             | 1 gpm              | 5 gpm                  |
| Housing Material:      | Polypropylene      | Polypropylene          |
| System Dimensions:     | 5.13" W x 12.23" H | 7.45" W x 23.22" H     |
| Cartridge Type:        | Carbon Block       | FibreDyne Carbon Block |
| Micron Rating:         | 1                  | 0.5                    |
| Capacity:              | 1,000 gal          | 15,000 gal             |
| Approx. Filter Life:   | 4-5 months         | 4-5 months             |
| Contaminant Reduction: | PFOA/PFOS          | PFOA/PFOS              |
| Certification:         | NSF/ANSI Std. 53   | NSF/ANSI Std. 53       |
| Feed Pressure Range:   | 0-125 psi          | 30-90 psi              |
| Temperature Range:     | 40°-100°F          | 40°-100°F              |
| Replacement Cartridge: | 655226-43          | 655223-43              |

## Installation and Operation Tips:

- Choose a mounting location suitable to support the full weight of the system while operating.
- Make sure to properly lubricate the O-ring prior to use.
- Install vertically with sump hanging down.
- Allow clearance below the cartridge for easy replacement.
- Replace cartridge if flow rate decreases.
- Do not exceed service flow rate.
- Inspect o-ring during each cartridge change. Lubricate or replace if necessary.
- Filter life dependent on gallon usage and overall incoming water quality.
- Please install a 5 micron sediment filter before these systems.

Chlorplus™ is a trademark of Pentair.