



GF20W with plug



GF20W NO plug

Mechanical Float Switch Features:

- Precision molded floats.
- Non-mercury design for potable and non-potable water applications.
- Float switches have 16 gauge CPE jacketed cords (SJOW-A/CSA Type SJOW), with 120 or 240 volt series piggy back plugs.
- Unterminated float switches for direct wire applications.
- CSA / UL approved.
- 13 Amps - 1/2 hp @ 120/240 VAC 60 Hz.
- Max operating temp: 140°F (60°C) water resistant, 194°F (90°C) dry.
- Black ABS floats for **PUMP DOWN** (normally open) or emptying applications.
- White ABS floats for **PUMP UP** (normally closed) or filling applications.



Part Number	Description	Cord & Plug	Application	Ctn Qty
MECHANICAL BLACK ABS FLOAT - PUMP DOWN/NORMALLY OPEN				
GF20W10F1	120V	10' with plug	Pump down	1
GF20W15F1	120V	15' with plug	Pump down	1
GF20W20F1	120V	20' with plug	Pump down	1
GF20W30F1	120V	30' with plug	Pump down	1
GF20W50F1	120V	50' with plug	Pump down	1
GF20W10F2	240V	10' with plug	Pump down	1
GF20W15F2	240V	15' with plug	Pump down	1
GF20W20F2	240V	20' with plug	Pump down	1
GF20W1000	120V/240V	10' NO plug	Pump down	1
GF20W1500	120V/240V	15' NO plug	Pump down	1
GF20W2000	120V/240V	20' NO plug	Pump down	1
GF20W3000	120V/240V	30' NO plug	Pump down	1
GF20W5000	120V/240V	50' NO plug	Pump down	1
MECHANICAL WHITE ABS FLOAT - PUMP UP/NORMALLY CLOSED				
GW2CW10F1	120V	10' with plug	Pump up	1
GW2CW15F1	120V	15' with plug	Pump up	1
GW2CW20F1	120V	20' with plug	Pump up	1
GW2CW30F1	120V	30' with plug	Pump up	1
GW2CW50F1	120V	50' with plug	Pump up	1
GW2CW10F2	240V	10' with plug	Pump up	1
GW2CW15F2	240V	15' with plug	Pump up	1
GW2CW20F2	240V	20' with plug	Pump up	1
GW2CW1000	120V/240V	10' NO plug	Pump up	1
GW2CW1500	120V/240V	15' NO plug	Pump up	1
GW2CW2000	120V/240V	20' NO plug	Pump up	1
GW2CW3000	120V/240V	30' NO plug	Pump up	1
GW2CW5000	120V/240V	50' NO plug	Pump up	1