


PVC MEDIUM "HOT" BLUE CEMENTS LO-VOC TURF-TITE

2400 Series BLUE

- Medium bodied, blue colored cement for PVC pipe and fitting. Up to 6" for Sch 40 and Sch 80.
- **Very fast setting cement formulated for wet conditions and/or quick pressurization and fast installation.**
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe and DWV.
- Irrigation installations.
- Fades to clear in sunlight.
- No primer needed on non-pressure DWV, where local codes permit.
- Recommended application temperature 40°F to 110°F. 
- Meets ASTM D-2564.
- Meets California Air Quality Management District and other environmental district rules.

Part Number	Size	Case Qty
2466S	4 oz.	24
2456S	8 oz.	24
2446S	16 oz.	24
2436S	32 oz.	12

PVC MEDIUM "HOT" BLUE CEMENTS LO-VOC POOL-TITE

**2300 Series
BLUE**

- Medium bodied, blue colored cement for PVC pipe and fittings. Up to 6" for Sch 40 and Sch 80.
- **Very fast setting cement formulated for wet conditions.**
- Recommended for ALL grades and types of PVC pipe and fittings, potable water, pressure pipe, gas, conduit, PVC flex pipe and DWV.
- **Color fades to clear in sunlight.**
- **No primer needed on non-pressure DWV, where local codes permit.**
- Recommended application temperature 40°F to 100°F.
- Works on flex to rigid pipe applications.
- Meets ASTM D-2564.
- Meets California Air Quality Management District and other environmental district rules.

Part Number	Size	Case Qty
2366S	4 oz.	24
2356S	8 oz.	24
2346S	16 oz.	24
2336S	32 oz.	12
2324	1 gallon	6