

PVC MEDIUM CLEAR FAST SET CEMENTS LO-VOCPOOL-CLEAR

**2900 Series
CLEAR**

- Medium bodied, clear cement for PVC pipe and fitting. Up to 6"
- Recommended for Sch 40 and Sch 80 pipe and fittings.
- Also recommended for PVC flex pipe.
- Meets ASTM D-2564.
- Meets California Air Quality Management District and other environmental district rules.



Part Number	Size	Case Qty
30875	4 oz.	24
2946S	16 oz.	24
2936S	32 oz.	12

CPVC MEDIUM ORANGE CEMENTS LO-VOC

**3200 Series
ORANGE**

- Medium bodied, orange colored cement for use on CPVC pipe and fittings. Up to 6"
- For copper tube size (CTS) and Sch 80, potable water pressure pipe.
- Recommended application temperatures down to 40°F to 110°F.
- Meets ASTM F-493.
- Meets California Air Quality Management District and other environmental district rules.



Part Number	Size	Case Qty
3256S	8 oz.	24
3236S	32 oz.	12

CPVC FLOWGUARD® GOLD™ LO-VOC 1-STEP YELLOW CEMENTS

319 Series

- Exceeds new environmental requirements and meets various CA district rules.
- For copper tube size (CTS) CPVC hot and cold potable water pipe and fittings up to 2" interference fit only.
- May be used without primer where local codes permit.
- For cold water systems and hot water systems up to 180°F.
- Faster cure time/reduced installation time.
- Meets ASTM F-493.
- Meets California Air Quality Management District and other environmental district rules.



Part Number	Size	Case Qty
31910	4 oz.	24
31911	8 oz.	24
31912	16 oz.	24