



11016



Super Lube Dri Lube (Dri-Film)

Super Lube Dri-Lube is a self-cleaning lubricant that actually cleans while lubricating. Super Lube Dri-Lube leaves behind a protective shield lubricant that will not attract dust. The dry coating provides a low coefficient of friction which gives excellent lubrication and release properties. Dri-Lube can be used on wood, metal and most plastics not under stress and has excellent thermal and chemical stability, forming a natural insulating barrier when used on electronics.

Benefits:

- Clean, non-staining
- For uses from -40°F to +500°F
- Non-conducting
- Easy to use
- Resists acid attacks
- Dries on contact
- Effective mold release agent
- Not affected by oil, water or solvents
- Long lasting lubrication
- Cleans while lubricating
- Stops squeaking, sticking
- Prevents corrosion

Applications:

- Industrial slides and glides
- High speed machinery
- Precision instruments
- Door and trunk hinges
- Pipe fittings
- Electronic & electrical equipment
- Chains
- Tools
- Zippers
- Lock cylinders
- Rusted nuts and bolts
- Cable pivots

Part Number	Description	Case Qty	List Price
11016	11 oz. aerosol	12	\$ 29.10



51010SL



51040

Super Lube Oil with PTFE

Super Lube Oil with PTFE is a premium synthetic oil with suspended PTFE particles that bond to surfaces to add lubricity to moving parts. Super Lube Oil with PTFE is used for applications which allow parts to be confined (ie. gear box). Use it as a general purpose lubricant for industrial machinery and equipment. Super Lube Oil with PTFE provides long life protection against friction, wear, rust and corrosion. Machinery lasts longer, downtime is reduced, and productivity is increased. Super Lube Oil with PTFE is safe on metal, rubber, plastic, wood, leather, fabric & painted surfaces.

Benefits:

- Waterproof
- Non-toxic (USDA rating H1)
- Synthetic with PTFE
- Reduces friction and wear
- Extends machinery & equipment life
- Reduces maintenance
- Viscosity stable
- Long-lasting

Applications:

- Plain, anti-friction & roller bearings
- Enclosed industrial gears
- Enclosed chains
- Gearhead motors
- Paper machines
- Conveyors
- Machine ways
- Reciprocating compressor lubricant additive
- Machine tools
- Centralized systems
- Straight, helical, bevel & spiral gears

Typical Properties:

Color: Translucent white
 Viscosity tested to ASTM D445
 cSt@ 100°F: 14-17
 cSt @ 40°F: 118-122
 ISO grade: 220
 Replaces ISO grade: 150-320
 Replaces SAE grade gear oils: 90
 Viscosity index: 145
 Shelf Life: 24 months

Part Number (old)	Description	Case Qty	List Price
51010SL (82333)	7 ml precision oiler	12	\$ 12.62
51040 (82334)	1 gallon	4	230.03